


**SEE
THE
LIGHT**




XAL

SEE THE LIGHT

We are passionate about the fascinating medium of light. XAL has focused on the medium in all its diversity, on its optimum adaptation to user requirements and on continual endeavours to roll back the borders of what is technically possible. The results are our aesthetic and functionally outstanding lighting solutions which can be perfectly integrated into all kinds of indoor and outdoor contexts.

In a dynamic environment with highest requirements we offer the necessary process quality, flexibility and internationality to develop sustainable concepts that go far beyond short-lived trends.





GENERAL
recessed (with trim / trimless)
6 different mounting housings
IP 20

LED
High-power LED
up to 420 lm, 106 lm/W per optic
3000 K, 4000 K, TW (3000-6000 K)
CRI ≥ 90
Binning initial ≤ 3 MacAdam

ESTIMATED LED LIFETIME
L80 / 50 000 h

OPTICAL
direct illumination (UGR < 19)
9 different optics
narrow spot 12°
round light distribution 35/55/75°
square light distribution 35/55/75°
rectangular light distribution 35x75°
wallwasher

ELECTRICAL
non DIM, DIM DALI, ZigBee 3.0


PHYSICAL
aluminium
powder-coated



The powerful and highly flexible UNICO multiple downlight combines up to nine individually controllable, small 38x38mm LED light insets, with varying emission characteristics and colour temperatures for creating a wide variety of lighting scenarios.

RECESSED SPOTLIGHTS


Mounting Housings



Dimensions

TYPE	WITH TRIM	CUTOUT	TRIMLESS	CUTOUT
L2	97x60 mm	90x52 mm	83x45 mm	99x62 mm
L4	173x60 mm	166x52 mm	158x45 mm	175x62 mm
L6	248x60 mm	241x52 mm	233x45 mm	250x62 mm
Q1	60x60 mm	52x52 mm	45x45 mm	62x62 mm
Q4	97x97 mm	89x89 mm	83x83 mm	99x99 mm
Q9	135x135 mm	127x127 mm	120x120 mm	137x137 mm


Optics



Features




50 mm
recess depth



micro-faceted
reflector



skimmed into plaster
board ceiling (trimless)



single control via
X-TALK app

MOVE IT 25 system

MODULAR PROFILE LIGHTING SYSTEMS

GENERAL
recessed trimless
ceiling mounted
suspended
IP 20

LED INSET OPAL
Mid-power LED
up to 3530 lm
up to 98 lm/W
3000 K
CRI > 90
Binning < 3-Step MacAdam

ESTIMATED LED LIFETIME
L80 / 50 000 h

OPTICAL
direct illumination
PMMA cover opal
asymmetric illumination


ELECTRICAL
48V power rail system
non DIM, DIM DALI, ZigBee 3.0

PHYSICAL
aluminium



MOVE IT 25 is a highly flexible system available for trimless installation in plasterboard ceilings, surface mounting on ceiling structures or as a suspended version with optional indirect light.

Mounting



Examples insets

JUST 32
FOCUS 17-43°



LUMINOUS FLUX
390lm (8w)

JUST 45



LUMINOUS FLUX
up to 730 lm

JUST 55



LUMINOUS FLUX
up to 2090 lm

**INSET 25 WALL
WASHER FLUSH**
L 300, 600, 1200, 2400mm



LUMINOUS FLUX
up to 2360 lm

**INSET 25 WALL
WASHER FLUSH**
L 300, 600, 1200, 2400mm




LUMINOUS FLUX
up to 3530 lm


Features



adjust. beam angle
17-43° (FOCUS)



170° Indirect
illumination



up to 6 node connections,
60-90° angle



single control via
X-TALK app

PROFILE 60

system



MODULAR PROFILE LIGHTING SYSTEMS

GENERAL
surface, suspended
IP20

LED
Mid-power LED
up to 2450 lm
up to 114 lm/W
3000K, 4000K
CRI ≥ 80
Binning initial ≤ 3 MacAdam

ESTIMATED LED LIFETIME
L80 / 50 000 h

OPTICAL
direct illumination
PMMA cover opal
microprismatic

ELECTRICAL
non DIM, DIM DALI
transparent feeder cable

PHYSICAL
aluminium
powdered-coated
halogen-free cable (internal wiring)



Circular segment of rolled aluminium profile, angular design with 55mm wide light emission, seamlessly welded; no visible screws; designed for continuous lighting systems

Mounting

OFFSET
RECESSED



RECESSED



CEILING



SUSPENDED



SUSPENDED
INDIRECT




Shapes

LINEAR



CORNER



CURVE



Light Distribution

OPAL



non DIM
power switch
3000 K / 4000 K

MICROPRISMATIC



DIM DALI
3000 K / 4000 K

WALLWASHER



DIM DALI
tunable white
3000 – 6000 K

SPOTLIGHT



non DIM, DIM DALI
emergency light
3000 K / 4000 K

LENO

surface / suspended

Refined technology

SURFACE MOUNTED AND SUSPENDED LUMINAIRES

GENERAL
surface mounted
suspended
IP 20
quick installation

LED
Mid-power LED
up to 2007 lm/m
up to 126 lm/W
3000 K, 4000k
CRI ≥ 80
Binning initial ≤ 3 MacAdam

ESTIMATED LED LIFETIME
L80 / 50 000 h

OPTICAL
direct light 100 %
HPO PMMA cover opal
microprismatic (UGR < 19)
jut-out PMMA cover


ELECTRICAL
DIM DALI
through wire included

PHYSICAL
aluminium
powder-coated
halogen-free cable (internal wiring)



Leno surface / suspended have an overall height of 28mm that can be used individually or as a system. It is simple to work with because of its easy mounting and magnetic fixing for the light inset.

Dimensions



Features



HPO PMMA cover
opal



microprismatic cover
(UGR < 19)




jut-out PMMA cover





magnetic holders for
tool-free mounting



flat design (28 mm)



quick installation



SURFACE MOUNTED AND SUSPENDED LUMINAIRES

GENERAL
surface mounted, suspended
inlay for TASK S SYSTEM
lightweight


ACOUSTIC
absorber
absorption class B

PHYSICAL
PET felt
colour range




This highly effective acoustic absorber, made of PET felt in four colour variants and formats, complements the versatile TASK luminaire series.

Dimensions




Features



NOD

suspended



GENERAL
suspended (rod)
IP 20

LED
Mid-power LED
up to 95 lm/W
2700 K, 3000 K
CRI ≥ 90
Binning initial ≤ 3 MacAdam

ESTIMATED LED LIFETIME
L80 / 50000 h

OPTICAL
direct light 100%
PMMA cover opal


ELECTRICAL
non DIM

PHYSICAL
soft touch coated surface
330° turnable, 180° tiltable


SUSPENDED

The sleek, minimalistic design of NOD by the young Japanese designer Daisuke Kitagawa strongly reflects the minimalist philosophy of his culture. The decorative fixture follows a traditional cone shape, but sets itself apart with an elegant black soft-touch surface.


Dimensions




Light Description



Features



330° rotatable



180° tiltable



available with
3-phase adapter



Exclusively Distributed By:

 **Cenit**
Illuminating Ways of Living

SHOWROOMS:

MAKATI

Unit 127 Makati Shangri-La Hotel Shopping Arcade, Ayala Avenue, Makati City
T: +[632] 818 4093 | F: +[632] 819 1549

MANILA

670 Florentino Torres Street, Sta. Cruz, Manila
T: +[632] 733 8351 to 56 | F: +[632] 734 1088

mail@cenitlighting.com
www.cenitlighting.com