



KALIX CONTACTLESS

Mains-fed Water Cooler

OASIS' classic KALIX has become fully CONTACTLESS.

Kalix Contactless uses advanced infrared sensors for an accessible gesture-based activation which also eliminates any concerns of cross-contamination from pathogens and viruses. This new technology provides all users with quick and easy water from a safe source.

Kalix Contactless provides two types of water temperature options. Ambient and cold or hot* and cold water options are available.



	AMBIENT & COLD	HOT & COLD
ACTIVATION	Contactless (Infrared sensor)	
SENSOR COVERAGE	Up to 18cm (approx.)	
FILTRATION	Green Filter (Optional), Built-in 100 micron strainer	
FLOW RATE	2.2 LPM	
DRAINAGE TYPE	Removable (Auto-drain available)	
EXTERIOR CHASSIS	ABS Plastic, Powder coated steel	
DIMENSIONS	Heavy Duty Galvanised Steel	
ALCOVE HEIGHT	1120(H) x 320(W) x 380(D) mm	
NET WEIGHT	23.4kg	24.6kg
INPUT POWER	220-240V, 50/60 Hz	
COOLING PERFORMANCE	20LPH (21°C amb.) / 8.5LPH (32°C amb.)	
TANK CAPACITY	Cold Tank 1.5L	Cold Tank 1.5L, Hot Tank 1.5L
TOTAL CURRENT	0.8A	2.8A
POWER CONS.	100W	620W
HEATING PERFORMANCE	-	7.9LPH
MODEL CODE	P1CPVCDKY	P1CPVCDHSY
COUNTRY OF ORIGIN	Poland	
CERTIFICATIONS	CE(LVD, EMC, RoHS)	
WARRANTY	1 Year	