



I-BEAM[®] IBG LED High Bay

The Most Configurable LED High Bay on the Market

Configurability and Efficiency Like Never Before

The I-BEAM[®] family of LED high bays from Lithonia Lighting[®] is among the most recognized and respected brands in the industry, with a proven track record of value and performance. This legacy continues with the IBG LED.

The versatile I-BEAM[®] IBG LED high bay boasts a single base platform design with the ability to select performance, optics, and housing options, taking IBG from basic applications to complex environments, including unconditioned spaces. The result is the maximum performance you need at the lowest possible cost. You no longer have to figure out 'which fixture', only 'what spec' YOU need!

One Platform + Your Spec = Incomparable Savings

No more "one size fits all", the I-BEAM[®] IBG allows you to specify and pay only for what you need for general or targeted illumination, code compliance and affordability. Maximizing the benefits of LED, IBG offers an incredible energy savings of up to 65% vs fluorescent and even more with HID, with maintenance-free operation. Its compact form factor and fewer components make the IBG easier to handle during installation, while high-efficiency options enable mounting heights up to 60'.

STOCK CONFIGURATIONS

Ci Code	Description	UPC
*240KNF	IBG 12L MVOLT	00190887180282
*240KNP	IBG 15L MVOLT	00190887180367
*240KNV	IBG 18L MVOLT	00190887180404
*240KP3	IBG 24L MVOLT	00190887180473

Configurability meets Performance.

- 8,000 to 60,000 lumens
- Standard and narrow fixture housing options
- High-ambient options up to 131°F (55°C)
- High efficiency options greater than 180+ LPW
- Narrow, general, wide & focus distributions
- Snap-Fit IP5X dust-resistant diffuse lens standard
- 3000K, 3500K, 4000K, 5000K; 80CRI (standard), 90CRI
- 120-480, MVOLT, HVOLT
- 0-10V dimming, Acuity Controls XPoint™ Wireless and nLight[®] options
- 6kV surge protection standard
- Emergency drivers provide up to 4,000 lumens

Taking design-build to a whole new level.

No more compromising or mixing-and-matching luminaire families to meet challenging specs. The I-BEAM IBG will give you many years of flexible, efficient lighting with an unprecedented, lowest total cost of ownership.

START WITH YOUR BASE					OPTIMAL MOUNTING HEIGHT				
	IBG	Lumens	Dimensions	Recommended Distributions	10'-20'	20'-30'	30'-40'	40'-50'	50'-60'
	2' 2-module	8000	11.75" W x 24" L	GND, WD	X				
	2' 4-module	12,000 / 15,000	15.5" W x 24" L	GND, WD	X	X			
	2' 6-module	18,000 / 24,000 / 30,000	20.65" W x 24" L	GND, ND		X	X		
	4' 2-module, Narrow	18,000 / 24,000 / 30,000 / 36,000	11.75" W x 48" L	GND, ND		X	X	X	
	4' 6-module	36,000 / 48,000 / 60,000	20.65" W x 48" L	GND, ND, FD			X	X	X

SELECT YOUR OPTIONS FOR MOUNTING, EMERGENCY BACKUP and CONTROLS					
Lumens	Housing	Performance Package	Lens	Distribution	Ambient
8L – 60L	Standard	SEF – Standard Eff	AFL – Acrylic Diffuse	General (GND)	Standard (45C)
	Narrow	HEF – High Eff	ACL – Acrylic Clear	Narrow (ND)	HA- High Ambient (55C)
			PFL- Polycarb Diffuse	Wide (WD)	
			PCL – Polycarb Clear	Focus (FD)	

Game-Changing Efficiency

Can your customers afford NOT to make the change?

COMPARISONS to TRADITIONAL FLUORESCENT			
Fixture	Wattage / Fixture	Watts Saved per Fixture	% SAVED
6-Lamp T5HO	365	-	-
IBG 24L HEF	130	235	65%
4-Lamp T5HO	236	-	-
IBG 18L HEF	100	136	58%
6-Lamp T8	214	-	-
IBG 15L HEF	85	145	60%

LUMENS PER WATT (LPW) REFERENCE				
I-BEAM * IBG	Standard Wattage	Standard LPW	Premium Wattage	Premium LPW
8000	54	146	49	170
12000	77	155	69	176
15000	95	157	86	180
18000	113	159	100	184
24000	150	159	133	185
30000	186	152	171	180
36000	221	151	197	183
48000	293	160	261	180
60000	374	153	323	183

(Based on 80CRI/5000K with diffuse lens, standard housings)

Configurability and Efficiency Like Never Before

The I-BEAM family of LED high bays from Lithonia Lighting is among the most recognized and respected brands in the industry, with a proven track record of value and performance. This legacy continues with the IBG LED.

The versatile I-BEAM IBG LED high bay boasts a single base platform design with the ability to select performance, optics, and housing options, taking IBG from basic applications to complex environments, including unconditioned spaces. The result is the maximum performance you need at the lowest possible cost. You no longer have to figure out 'which fixture', only 'what spec' YOU need!

One Platform + Your Spec = Incomparable Savings

No more "one size fits all", the I-BEAM IBG allows you to specify and pay only for what you need for general or targeted illumination, code compliance and affordability. Maximizing the benefits of LED, IBG offers an incredible energy savings of up to 65% vs fluorescent and even more with HID, with maintenance-free operation. Its compact form factor and fewer components make the IBG easier to handle during installation, while high-efficiency options enable mounting heights up to 60'.

STOCK CONFIGURATIONS		
Ci Code	Description	UPC
*240KNF	IBG 12L MVOLT	00190887180282
*240KNP	IBG 15L MVOLT	00190887180367
*240KNV	IBG 18L MVOLT	00190887180404
*240KP3	IBG 24L MVOLT	00190887180473

Configurability meets Performance.

- 8,000 to 60,000 lumens
- Standard and narrow fixture housing options
- High-ambient options up to 131°F (55°C)
- High efficiency options greater than 180+ LPW
- Narrow, general, wide & focus distributions
- Snap-Fit IP5X dust-resistant diffuse lens standard
- 3000K, 3500K, 4000K, 5000K; 80CRI (standard), 90CRI
- 120-480, MVOLT, HVOLT
- 0-10V dimming, Acuity Controls XPoint™ Wireless and nLight™ options
- 6kV surge protection standard
- Emergency drivers provide up to 4,000 lumens

SHOWROOM:

670 Florentino Torres Street, Sta. Cruz, Manila
T: +(632) 8733 8351 to 52 | M: +(63) 915 6024856 +(63) 9175615922

HEAD OFFICE:

2/F Le Mar Ben II Building 747 San Bernardo Street, Sta. Cruz, Manila
T: +(632) 8733 8353 to 56 | M: +(63) 917 55-CENIT (23648)