



brite

Essential Lighting

Solutions



DOWNLIGHTS • TRACKLIGHTS
TROFFERS • LINEAR

PARKING LIGHTING

EMERGENCY LIGHTS
EXIT SIGNS



Lloyd_H204K

Fixed / Recessed



| | |
|------------------|--------|
| Dimension (mm) : | 125Ø |
| Beam Angle : | 30° |
| Lumens : | 1900lm |
| Watts : | 20W |
| CCT : | 4000K |
| CRI : | 80 |
| IP Rating : | IP20 |



Lloyd_IP

Fixed / Recessed

| | | |
|------------------|--------|--------|
| Dimension (mm) : | 85Ø | 85Ø |
| Beam Angle : | 30° | 30° |
| Lumens : | 1200lm | 1200lm |
| Watts : | 14W | 14W |
| CCT : | 3000K | 4000K |
| CRI : | 80 | 80 |
| IP Rating : | IP65 | IP65 |

Lloyd_AR

Fixed / Recessed



| | | | |
|------------------|--------|--------|--------|
| Dimension (mm) : | 85Ø | 113Ø | 145Ø |
| Beam Angle : | 40° | 50° | 60° |
| Lumens : | 1300lm | 1500lm | 2500lm |
| Watts : | 13W | 13W | 28W |
| CCT : | 3000K | 3000K | 3000K |
| CRI : | 80 | 80 | 80 |
| IP Rating : | IP20 | IP20 | IP20 |



Lloyd_ARD

Directional / Recessed

| | | |
|------------------|--------|--------|
| Dimension (mm) : | 151Ø | 151Ø |
| Beam Angle : | 24° | 45° |
| Lumens : | 2000lm | 2930lm |
| Watts : | 25W | 35W |
| CCT : | 3000K | 3000K |
| CRI : | 80 | 80 |
| IP Rating : | IP20 | IP20 |

Lloyd_ARID

Fixed / Recessed



| | |
|------------------|--------|
| Dimension (mm) : | 160Ø |
| Beam Angle : | 60° |
| Lumens : | 1700lm |
| Watts : | 26W |
| CCT : | 3000K |
| CRI : | 80 |
| IP Rating : | IP20 |



Lloyd_ARD2

Directional / Recessed

| | | |
|------------------|--------|--------|
| Dimension (mm) : | 100Ø | 138Ø |
| Beam Angle : | 15° | 40° |
| Lumens : | 1500lm | 1800lm |
| Watts : | 13W | 19.5W |
| CCT : | 3000K | 3000K |
| CRI : | 80 | 80 |
| IP Rating : | IP20 | IP20 |

Lloyd_RS

Fixed / Recessed



| | | | |
|------------------|-------|-------|-------|
| Dimension (mm) : | 95Ø | 170Ø | 200Ø |
| Beam Angle : | 110° | 110° | 110° |
| Lumens : | 280lm | 620lm | 660lm |
| Watts : | 5.5W | 11W | 12.5W |
| CCT : | 5500K | 3000K | 3000K |
| CRI : | 80 | 80 | 80 |
| IP Rating : | IP20 | IP20 | IP20 |



Lloyd_ARW

Wall Washer / Recessed / Dimmable

| | |
|------------------|--------|
| Dimension (mm) : | 115Ø |
| Beam Angle : | 40° |
| Lumens : | 1500lm |
| Watts : | 13W |
| CCT : | 3000K |
| CRI : | 80 |
| IP Rating : | IP20 |

Frank LED Downlights - Square Series

Frank_ARW

Wall Washer / Recessed / Dimmable



| | | |
|------------------|-------|---------|
| Dimension (mm) : | 85x85 | 115x115 |
| Beam Angle : | 24° | 36° |
| Lumens : | 900lm | 1300lm |
| Watts : | 9W | 13W |
| CCT : | 3000K | 3000K |
| CRI : | 80 | 80 |
| IP Rating : | IP20 | IP20 |



Frank_ARF

Fixed / Recessed

| | | |
|------------------|--------|---------|
| Dimension (mm) : | 90x90 | 115x115 |
| Beam Angle : | 60° | 60° |
| Lumens : | 1500lm | 2000lm |
| Watts : | 13W | 18.5W |
| CCT : | 3000K | 3000K |
| CRI : | 80 | 80 |
| IP Rating : | IP20 | IP20 |

Frank_SS

Fixed / Recessed



| | | | | |
|------------------|---------|---------|---------|---------|
| Dimension (mm) : | 100x100 | 150x150 | 180x180 | 250x250 |
| Beam Angle : | 110° | 110° | 110° | 110° |
| Lumens : | 230lm | 560lm | 770lm | 1320lm |
| Watts : | 5.5W | 11W | 14W | 22.5W |
| CCT : | 3000K | 3000K | 3000K | 3000K |
| CRI : | 80 | 80 | 80 | 80 |
| IP Rating : | IP20 | IP20 | IP20 | IP20 |



Frank_ARD

Directional / Recessed

| | |
|------------------|---------|
| Dimension (mm) : | 100x100 |
| Beam Angle : | 20° |
| Lumens : | 1300lm |
| Watts : | 13W |
| CCT : | 3000K |
| CRI : | 80 |
| IP Rating : | IP20 |

Norman Multi Directional LED Tracklight Series

Norman_ARG1V

Track Rail Mounting



Dimension (mm) : 106Ø
 Beam Angle : 15°
 Lumens : 2500lm
 Watts : 25W
 CCT : 3000K
 CRI : 80
 IP Rating : IP20

Norman_ARG2T

Track Rail Mounting



| | | |
|----------------------|--------|--------|
| Dimension (mm) : 60Ø | 60Ø | 60Ø |
| Beam Angle : 24° | 24° | 24° |
| Lumens : 1200lm | 1800lm | 1800lm |
| Watts : 14W | 28W | 28W |
| CCT : 4000K | 3000K | 4000K |
| CRI : 80 | 80 | 80 |
| IP Rating : IP20 | IP20 | IP20 |

Norman_ARG1T

Track Rail Mounting



Dimension (mm) : 106Ø
 Beam Angle : 15°
 Lumens : 2500lm
 Watts : 15W / 30W
 CCT : 3000K
 CRI : 80
 IP Rating : IP20

Norman_ARG2V

Track Rail Mounting



Dimension (mm) : 106Ø
 Beam Angle : 125°
 Lumens : 1200lm
 Watts : 20W
 CCT : 3000K
 CRI : 80
 IP Rating : IP20

Norman_ARG1H

Track Rail Mounting



Dimension (mm) : 106Ø
 Beam Angle : 15°
 Lumens : 2500lm
 Watts : 25W
 CCT : 3000K
 CRI : 80
 IP Rating : IP20



Reflex LED Troffer Series

Reflex_T


Recessed / Suspended



Dimension (mm) : 600x620
 600x1220
 Lumens : 3000lm / 6500lm
 Watts : 24W / 50W
 CCT Settable : 3000K / 4000K / 5000K
 CRI : 80
 IP Rating : IP20

Reflex_P

Recessed / Suspended



Dimension (mm) : 595x595
 595x1195
 Lumens : 4000 / 6500lm
 Watts : 36W
 CCT Settable : 4000K / 5000K / 6500K
 CRI : 80
 IP Rating : IP20

Reflex LED Linear Series

Reflex_L

Suspended / Surface



Dimension (mm) : 1135x82x62
 Lumens : 2100lm / 2800lm
 Watts : 30W
 CCT Settable : 4000K / 5500K
 CRI : 80
 IP Rating : IP20

brite
T E C H

Halver LED Parking Lighting



Dimension (mm) : 1225x85
 Lumens : 2300 / 4700lm
 Watts : 18W / 36W
 CCT Settable : 3000K / 4000K / 6500K
 CRI : 80
 IP Rating : IP65



Phoenix LED Emergency Lights Series

Phoenix_MINI Wall Surface



Lumens Output : 200lm
 Wattage : 2 x 1W
 Duration Time : Approx. 180 minutes
 Voltage : 220-240V, 60Hz
 Battery : 3.6V, 1000mAh Ni-Cad
 Material : ABS Housing
 IP Rating : IP20

Phoenix_RD Ceiling Recessed



Lumens Output : 200lm
 Wattage : 2W
 Duration Time : Approx. 180 minutes
 Voltage : 220-240V, 60Hz
 Battery : 3.6V, 2000mAh Ni-Cad
 Material : PC Housing
 IP Rating : IP20

Phoenix_AB Wall Surface



Lumens Output : 300lm
 Wattage : 2 x 1.2W
 Duration Time : Approx. 90 minutes
 Voltage : 120-277V, 60Hz
 Battery : 6V, 4AH Lead Acid Bat
 Material : ABS Housing
 IP Rating : IP20

Phoenix_IP Wall Surface



Lumens Output : 500lm
 Wattage : 6.8W
 Duration Time : Approx. 240 minutes
 Voltage : 220-240V, 60Hz
 Battery : 12V, 2800mAh Ni-Cad
 Material : ABS Housing
 IP Rating : IP65

Phoenix_HO Wall Surface



Lumens Output : 650lm
 Wattage : 2 x 4W
 Duration Time : Approx. 90 minutes
 Voltage : 120-277V, 60Hz
 Battery : 6V, 4AH Lead Acid Bat
 Material : ABS Housing
 IP Rating : IP20



Orion LED Exit Sign Series

Orion_MC Wall / Ceiling Mounted



Duration Time : Approx. 360 minutes
 Voltage : 120-277V, 60Hz
 Battery : 3.6V, 600mAh Ni-Cad
 Material : Aluminum Housing
 IP Rating : IP20

Orion_AB Wall / Ceiling Mounted



Duration Time : Approx. 360 minutes
 Voltage : 220-240V, 60Hz
 Battery : 1.2V, 1000mAh Ni-Cad
 Material : ABS Housing
 IP Rating : IP20

Orion_MB Wall / Ceiling Mounted



Duration Time : Approx. 360 minutes
 Voltage : 120-277V, 60Hz
 Battery : 3.6V, 600mAh Ni-Cad
 Material : Aluminum Housing
 IP Rating : IP20

Orion_IP Wall / Ceiling Mounted



Duration time : Approx. 360 minutes
 Voltage : 220-240V, 60Hz
 Battery : 3.6V, 500mAh Ni-Cad
 Material : ABS Housing
 IP rating : IP65

Orion_RM Wall / Ceiling Mounted



Duration Time : Approx. 360 minutes
 Voltage : 220-240V, 60Hz
 Battery : 3.6V, 1000mAh Ni-Cad
 Material : Aluminum Housing
 IP Rating : IP20



SHOWROOM:

670 Florentino Torres Street, Sta. Cruz, Manila
 T: +{632} 8733 8351 to 52 | M: +{63} 915 6024856

HEAD OFFICE:

2/F Le Mar Ben II Building 747 San Bernardo Street, Sta. Cruz, Manila
 T: +{632} 8733 8353 to 56 | M: +{63} 917 55-CENIT {23648}